



## 3.5 kW Wind Turbine System Specification Sheet

Wind is a naturally occurring and abundant resource and is one of the cleanest ways to produce electricity. Very little processing needs to be done to convert it into clean, free energy. Operation of our wind turbines produces no pollution with no emissions, excessive noise or waste heat by-products. Wind can be harvested with minimal impact on the environment, a very important factor in meeting our increasing energy needs.

### Synergy

- Solar
- Biomass
- Diesel Generator
- Hydroelectric
- Geothermal

### Applications


- Commercial and Industrial
- Residential and Resort
- Agricultural
- Remote Communities
- Off-Grid Power
- Institutional and Public

### Key Benefits

- Energy cost savings from wind generated power
- No scheduled maintenance
- Designed to reliably operate in harsh cold & hot climates
- Operation creates virtually no environmental impact
- Cost-effective and financially viable
- 5-Year Warranty

### Turbine

Rated Power Output	3.5 kW
Energy Production*	500 kWh/month
Type	5 blades, downwind
Generator	Gearless, brushless, permanent magnet
Swept Area	12.6 m <sup>2</sup>
Blade Diameter	4 m
Blade Material	Fibreglass reinforced plastic
Total Turbine Mass	68 kg
Voltage/Phase @ Rated Power	150 Vac peak
Current/Phase @ Rated Power	8 Aac peak
Generator NEMA Rating	Class F, 5 HP
Life Expectancy	> 20 years
*5.0 m/s (18 km/h) average wind speed, Rayleigh Distribution, Sea Level elevation	



### Operational Data

Rated Wind Speed	11 m/s (39 km/h)
Start-up Wind Speed	2.8 m/s (11 km/h)
Braking Wind Speed	15 m/s (55 km/h)
Furling Method	EM Brake
RPM at Rated Power	350 RPM
Survival Wind Speed	50 m/s (180 km/h)
Survival RPM	1,000 RPM

# A Revolution in Wind Energy

## Inverter

Type	Raum3500i Grid-tie
Input Power Rating	3.5kW
Electrical Input	Three-phase
Rated Input Voltage	150 Vac peak/phase
Rated Input Current	8 Aac peak/phase
Output Voltage	240 Vrms True Sine Wave
Max Output Current	15 Arms True Sine Wave
Power Factor at Output	>0.99
Certifications	CSA 22.2 #107.1 and UL 1741
Enclosure Weight	10 kg per unit
Size	330 mm x 300 mm x 100 mm

## System Power Curve

Wind Speed (m/s)	Power Out (W): Grid-tie
3	51
4	134
5	297
6	563
7	1000
8	1569
9	2233
10	3064
11	3500
12	3500

## Tower

Tower Type	Engineered free-standing steel monopole
Installation Method	Gin pole; no crane required
Foundation	3 m <sup>3</sup> concrete (varies with region standard)
Number of Sections	4 x 3.7 m (12') sections
Tower Height to Nacelle	14.5 m (48')
Tower Mass	410 kg (900 lbs)
Max Lateral Load at Mast	5000 N (1120 lbs)
Max Vertical Load at Mast	880 N (200 lbs)
Survival Wind Speed*	50 m/s (180 km/h)

\*With 5000 N (1120 lbs) loading at mast tip

## Annual Energy Production

Wind Speed (m/s)	kWh/year: Grid-tie
4	2992
4.5	4390
5	6220
5.5	7498
6	9467
6.5	10,994
7	12,292
7.5	13,837



Toll Free. 1-877-946-3979  
Ph. (306) 651-1476  
sales@raumenergy.com  
www.raumenergy.com

3718A Millar Ave  
Saskatoon, SK  
S7P 0B1  
Canada